

NAME

`latexdiff-vc` – wrapper script that calls `latexdiff` for different versions of a file under version management (CVS, RCS or SVN)

SYNOPSIS

latexdiff-vc [*latexdiff-options*] [*latexdiff-vc-options*] **-r** [*rev1*] [**-r** *rev2*] *file1.tex* [*file2.tex* ...]

or

latexdiff-vc [*latexdiff-options*] [*latexdiff-vc-options*] [**--postscript** | **--pdf**] *old.tex new.tex*

DESCRIPTION

latexdiff-vc is a wrapper script that applies *latexdiff* to a file, or multiple files under version control (git, subversion (SVN), mercurial (hg), CVS, RCS), and optionally runs the sequence of `latex` and `dvips` or `pdflatex` commands necessary to produce pdf or postscript output of the difference tex file(s). It can also be applied to a pair of files to automatise the generation of difference file in postscript or pdf format.

OPTIONS

--rcs, **--svn**, **--cvs**, **--git** or **--hg**

Set the version control system used. If no version system is specified, `latexdiff-vc` will venture a guess.

`latexdiff-cvs`, `latexdiff-rcs` etc are variants of `latexdiff-vc` which default to the respective versioning system. However, this default can still be overridden using the options above.

Note that hg needs to support the `--root` option (version ≥ 2.9)

-r, **-r** *rev* or **--revision**, **--revision=rev**

Choose revision (under RCS, CVS, SVN, GIT or HG). One or two **-r** options can be specified, and they result in different behaviour:

latexdiff-vc **-r** *file.tex* ...

compares *file.tex* with the most recently checked-in version checked.

latexdiff-vc **-r** *rev1* *file.tex* ...

compares *file.tex* with revision *rev1*.

latexdiff-vc **-r** *rev1* **-r** *rev2* *file.tex* ...

compares revisions *rev1* and *rev2* of *file.tex*.

Multiple files can be specified for all of the above options. All files must have the extensions `.tex`, `.bbl`, or `.flt`, though.

latexdiff-vc *old.tex new.tex*

compares two files.

The name of the difference file is generated automatically and reported to stdout.

-d or **--dir** **-d** *path* or **--dir=***path*

Rather than appending the string `diff` and optionally the version numbers given to the output-file, this will prepend a directory name `diff` to the original filename, creating the directory and sub-directories should they not exist already. This is particularly useful in order to clone a complete directory hierarchy. Optionally, a pathname *path* can be specified, which is prepended instead of `diff`.

--flatten,--flatten=keep-intermediate

If combined with `--git`, `--svn` or `--hg` option or the corresponding modes, check out the revisions to compare in a separate temporary directory, and then pass on option `--flatten` to `latexdiff`. The directory in which `latexdiff-vc` is invoked defines the subtree which will be checked out. Note that if additional files are needed which are not included in the flatten procedure (package files, included graphics), they need to be accessible in the current directory. If you use `bibtex`, it is recommended to include the `.bbl` file in the version management. From `latexdiff-vc >=1.3.4` there is an attempt to create the `.bbl` file by running `bibtex` in the retrieved subdirectories; note that the `bibtex` is run in the temporary subdirectories so any `.bib` or `.bst` files either need to be under version management, or in the global search paths for `bibtex` (shell environment variables `BIBINPUTS` and `BSTINPUTS`).

The generic usage of this function is: `latexdiff-vc --flatten -r rev1 [-r rev2] master.tex` where `master.tex` is the project file containing the highest level of includes etc.

With `--flatten=keep-intermediate`, the intermediate revision snapshots are kept in the current directory (Default is to store them in a temporary directory and delete them after generating the diff file.)

--only-changes

Post-process the output such that only pages with changes on them are displayed. This requires the use of subtype `ZLABEL` in `latexdiff`, which will be set automatically, but any manually set `-s` option will be overruled (also requires `zref` package to be installed). This option also disables internal links (as implemented by `hyperref` package) and graphics markup. (note that this option must be combined with `--ps` or `--pdf` to make sense)

--force

Overwrite existing diff files without asking for confirmation. Default behaviour is to ask for confirmation before overwriting an existing difference file.

--run

run latex command on diff file after generation of diff file.

--dvi

run latex and dvixxx commands after generation of diff file.

-c configfile =item --config var1=val1,var2=val2,... or -c var1=val1,..

Set configuration variables for `latexdiff` and `latexdiff-vc`. The option can be repeated to set different variables (as an alternative to the comma-separated list). Available variables for `latexdiff-vc`:

`LATEXDIFF` `latexdiff` command (e.g. `latexdiff-fast`, `latexdiff-so`). This command should support the options `-draftmode` and `-interaction=batchmode`

`LATEX` latex command (e.g. `pdflatex`, `lualatex`)

`DVI2` Command for conversion of dvi file (e.g. `dvips`, `dvipdf`)

`BIBTEX` Command replacing `bibtex`

All other config variables are passed to `latexdiff`. Explicitly set configuration changes always override implicit changes by the following shortcut options **--fast**, **--so**, **--ps** and **--pdf**.

--fast or --so

Use `latexdiff-fast` or `latexdiff-so`, respectively (instead of `latexdiff`).

--ps or --postscript

Generate postscript output from difference file. This will run the sequence `latex; latex; dvips` on the difference file (do not use this option in the rare cases, where three `latex` commands are required if you care about correct referencing). If the difference file contains a `\bibliography` tag, run the sequence `latex; bibtex; latex; latex; dvips`.

--pdf

Generate pdf output from difference file using `pdflatex`. This will run the sequence `pdflatex; pdflatex` on the difference file, or `pdflatex; bibtex; pdflatex; pdflatex` for files requiring `bibtex`. Note that this is not just a shortcut for setting configuration variable but also triggers some special behaviour.

--show-config

Show values of configuration variables.

--help or -h

Show help text

--version

Show version number

All other options are passed on to `latexdiff`. Note that it is not always easy for `latexdiff` to correctly assign arguments to options when short form (single letter) options are used so it is recommended to use long-form options.

SEE ALSO

`latexdiff`

PORTABILITY

latexdiff-vc uses external commands and is therefore dependent on the system architecture; it has been tested mainly on Unix-like systems. It also requires a version control system and `latex` to be installed on the system to make use of all features. Modules from Perl 5.8 or higher are required.

BUG REPORTING

Please submit bug reports using the issue tracker of the github repository page <https://github.com/tilmann/latexdiff.git>, or send them to *tilmann* — AT — *gfz-potsdam.de*. Include the version number of *latexdiff-vc* (option `--version`).

AUTHOR

Version 1.3.4a Copyright (C) 2005–2017 Frederik Tilmann

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License Version 3 Contributors: S Utcke, H Bruyninckx; some ideas have been inspired by `git-latexdiff` bash script. C. Junghans: Mercurial Support.